

PRODUCT NAME: HIGH GLOSS LEMON YELLOW
PRODUCT CODE: 290155 (SEE ADDRESS)

HMIS CODES: H F R P
1 2 0

MANUFACTURER'S NAME: BENNETTE PAINT MANUFACTURING COMPANY, INC.
ADDRESS: 401 Industry Drive, Hampton, Virginia 23661
EMERGENCY PHONE: 804-838-7777

DATE PREPARED: 05-09-91
INFORMATION PHONE: 804-838-7777
NAME OF PREPARER: Bennette Paint Mfg. Co., Inc.

HAZARDOUS COMPONENTS	CAS NUMBER	OSHA PEL	ACGIH TLV	OTHER	VAPOR PRESSURE mm Hg @ 15°C	WEIGHT PERCENT
HAZARDOUS COMPONENTS	9052-41-3	100 ppm	NR	NR	10.0	77%
MINERAL SPARKS						51.34

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 300 deg F V.P.C.: 4.16 LB/AL (499 GR/L) SPECIFIC GRAVITY (20°C): 1.0
 VAPOR DENSITY: HEAVIER THAN AIR SOLUBILITY IN WATER: Insoluble EVAPORATION RATE: SLOWER THAN OTHER
 APPEARANCE AND ODOR: Viscous liquid. Mild odor. WEIGHT PER GALLON: 8.13

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 100 deg F METHOD USED: ICC FLAMMABLE LIMITS IN AIR BY VOLUME: LOWER: 0.9% UPPER: 7.0%
 EXTINGUISHING MEDIA: Foam, CO2, dry chemical, water fog

SPECIAL FIREFIGHTING PROCEDURES: Use air-supplied rescue equipment for enclosed areas. Cool exposed containers with water spray. Avoid breathing vapor or fumes.
 UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from heat, sparks, and open flames. Fight as volatile liquid fire. Use water to keep fire-exposed containers cool to reduce pressure.

SECTION V - REACTIVITY DATA

STABILITY: STABLE
 CONDITIONS TO AVOID: Extreme heat or humidity. Any source of ignition.
 INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with strong oxidizing agents.
 HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Usual products of combustion-CO, CO2, and possible acrolein.
 HAZARDOUS POLYMERIZATION: WILL NOT OCCUR None

SECTION VI - HEALTH HAZARD DATA

IRRRADIATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Temporary dizziness, headache, possible nausea; symptoms disappear when exposure ceases.
 SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Eye or skin contact may cause discomfort by defatting action of solvent. Repeated contact to skin may cause dermatitis.
 SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: See above
 INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Do not ingest.

HEALTH HAZARDS (ACUTE AND CHRONIC): Inhalation: Temporary dizziness, headache, possible nausea; symptoms disappear when exposure ceases. Eye or skin contact may cause discomfort by defatting action of solvent. Repeated contact to skin may cause dermatitis.
 CARCINOGENICITY: N/A NTP? No IARC MONOGRAPHY? No OSHA REGULATED? Yes
 MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Any existing respiratory or cardiovascular ailment.

EMERGENCY AND FIRST AID PROCEDURES: If overcome by vapor, remove from exposure immediately; call a physician. If breathing is irregular or stopped, start resuscitation, administer oxygen. If ingested, DO NOT induce vomiting; call a physician. In case of skin contact, remove contaminated clothing, and wash skin thoroughly. If splashed into eyes, flush eyes with clean water for 15 minutes or until irritation subsides. If irritation persists, seek medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED FOR SPILLED: Remove sources of ignition and provide ventilation. Large spills may be set up with non-sparking tools. Provide respiratory protection if required. Small quantities may be picked up with absorbent material.
 WASTE DISPOSAL METHOD: In accordance with local, state, and federal regulations.
 PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store away from heat, sparks, and open flame. Avoid prolonged skin contact. DO NOT breathe spray mist. Combustible liquid, class II.

OTHER PRECAUTIONS: Ground containers when pouring and limit free fall to a few inches to prevent static sparks. Avoid spontaneous combustion of contaminated rags and other easily ignitable organic accumulations by immediate immersion in water. Empty containers retain hazardous properties. DO NOT cut, puncture, or weld on or near containers. Keep away from children.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: Approved mask or respirator for organic vapors.
 VENTILATION: Ventilation should be designed and maintained to provide volume and pattern sufficient to prevent vapor concentration in excess of TLV or PEL.
 PROTECTIVE GLOVES: Neoprene rubber gloves.
 EYE PROTECTION: goggles or side shield spectacles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye wash station and safety showers should be available.
 WORK/HYGIENE PRACTICES: Wash hands after use and before eating or using washrooms.

SECTION IX - DISCLAIMER

Bennette Paint Mfg. believes that the information contained in this MSDS is correct as of this date. However, because the material may be used under conditions over which Bennette Paint Mfg. has no control or in ways we can not anticipate, we give no warranty, expressed or implied, as to the accuracy of the information and assume no responsibility for any damage.

APPENDIX

APPENDIX DATE OF PREPARATION: 05-20-91
 PRODUCT NUMBER: 290154, 290155, 290156, 290539
 PRODUCT NAME: High Gloss Lemon Yellow

Bennett's
02-15-91