Permatex, Inc. 10 Columbus Blvd. Hartford, CT 06106 USA Telephone: 1-87-Permatex

(877) 376-2839

Emergency: 800-255-3924

International Emergency: 813-348-0585

# 100626

## NOTØNTAI Material Safety Data Sheet NOTNT216

#### 1. PRODUCT IDENTIFICATION

**Product Name:** 

**Product Type:** 

NO TOUCH ORIGINAL TIRE CARE 210Z AE

Item No:

Aerosol cleaner

NT21-6

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
Water 7732-18-5	70-80	Not Listed	Not Listed
SILICONE EMULSION MIXTURE	5-15	Not Listed	Not Listed
Glycerin 56-81-5	1-10	Not Listed	Not Listed
PETROLEUM GASES, LIQUEFIED, SWEETENED 68476-86-8	1-10	1000 ppm TWA	Not Listed
POLYDIMETHYLSILOXANE 63148-62-9	1-10	Not Listed	Not Listed
SORBITOL 50-70-4	1-10	Not Listed	Not Listed

#### 3. HAZARDS IDENTIFICATION

May cause eye, skin and respiratory irritation. Intentional misuse by concentrating and inhaling the

vapor may be harmful or fatal.

Primary Routes of Entry:

Eye and skin contact, ingestion, inhalation. Signs and Symptoms of Exposure: May cause redness to eyes and irritation to nasal passages. Excessive accidental exposure may

cause headache, dizziness, nausea and mild respiratory irritation.

Medical Conditions Recognized as None known

**Being Aggravated by Exposure:** 

#### 4. FIRST AID MEASURES

Ingestion:

Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation:

If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention..

**Skin Contact:** 

Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical

**Eye Contact:** 

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical

attention if irritation persists.

#### 5. FIRE FIGHTING MEASURES

Flash Point (°F/C):

Recommended Extinguishing Media:

**Special Fire-Fighting Procedures:** 

**Hazardous Products Formed by Fire or Thermal** 

**Decomposition:** 

Unusual Fire/Explosion Hazards:

No flame projection

Carbon Dioxide, Dry Chemicals, Foam.

Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Carbon monoxide, Carbon dioxide,

Exposure to temperatures over 120 degrees F. may cause bursting or venting. Keep containers coel. Use equipment or shielding to protect personnel from bursting containers.

Lower Explosive Limit: **Upper Explosive Limit:** 

2.2% 9.5%

210Z AE

#### 6. ACCIDENTAL RELEASE MEASURES

**Spill Procedures:** Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a

closed waste container until disposal. Flush spill or leak area with water.

#### 7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F.

Exposure to high temperatures may cause container to burst. Store in accordance with NFPA 30B for

Level 1 Aerosols.

Avoid contact with skin and eyes. Intentionally concentrating and inhaling the vapor may be harmful or fatal. Use only in a well ventilated area. Product may cause surfaces to become slippery. Handling:

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Not normally required, but wearing safety glasses will minimize exposure. Recommended if handling large spills.

Skin:

Ventilation:

Not normally necessary. Recommended if handling large spills.

Mechanical ventilation.

**Respiratory Protection:** If handling large industrial or warehouse spills, wear NIOSH-approved respiratory protection.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Odor:

White foam MINIMAL

**Boiling Point (°F):** pH:

212°F

Solubility in Water:

9.0-10.0 SOLUBLE

**Specific Gravity:** VOC Content(Wt.%): 1.015-1.025 Approximately 5% by weight

**Vapor Pressure:** Vapor Density (Air=1): 70psig @ 70 degrees F.

**Evaporation Rate:** 

>1 (air = 1) <1 (butyl acetate = 1)

## 10. STABILITY AND REACTIVITY

**Chemical Stability:** 

Stable at normal conditions

**Hazardous Polymerization:** Incompatabilities:

WILL NOT OCCUR

Strong oxidizers. Do not expose to heat or store at temperatures above 120 F.

Conditions to Avoid: **Hazardous Products Formed by Fire or Thermal** 

Carbon monoxide, Carbon dioxide,

**Decomposition:** 

## 11. TOXICOLOGICAL INFORMATION

See Section 3

#### 12. ECOLOGICAL INFORMATION No data available

#### 13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and

discard in the trash. Follow Canadian and local regulations for disposal.

D001 as per 40CFR 261.21

**US EPA Waste Number:** 

## 14. TRANSPORTATION INFORMATION

**DOT (49CFR 172)** 

**Domestic Ground Transport DOT Shipping Name:** 

CONSUMER COMMODITY

**Hazard Class: UN/ID Number:**  ORM-D None

**Marine Pollutant:** 

None

**IATA** 

**Proper Shipping Name:** 

Consumer Commodity

**Class or Division:** 

2 of 3

Product name: NO TOUCH ORIGINAL TIRE CARE 210Z AE

**UN/NA Number:** 

ID 8000

**IMDG** 

Proper Shipping: **Hazard Class:** 

Aerosols, Limited Quantity

Class 2.2 **UN Number:** UN 1950

15. REGULATORY INFORMATION SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

**SARA 313 Information** 

NONE

**CALIFORNIA PROP 65:** 

No California Prop 65 chemicals are known to be present.

**TSCA inventory Status:** 

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

**16. OTHER INFORMATION** 

Estimated NFPA Rating: Estimated HMIS Classification:

HEALTH 1, FLAMMABILITY 4, REACTIVITY 0

HEALTH 1, FLAMMABILITY 4, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn. HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By:

Denise Boyd, Health and Safety Manager

Revision Date: 03/01/2004 Revision

Company:

Permatex. Inc. 10 Columbus Blvd. Hartford, CT USA

Number:

**Telephone Number:** 1-87-Permatex (877) 376-2839