

# MATERIAL SAFETY DATA SHEET

## Section 1: Product & Company Identification

**Product Name:** Siloo® De-Squeak™

**Product Number (s):** 60A

**Manufactured By:** CRC Industries, Inc. (215) 674-4300  
885 Louis Drive, Warminster, PA 18974  
24-Hour Emergency Information: CHEMTREC (800) 424-9300

## Section 2: Composition/Information on Ingredients

Component	CAS NUMBER	ACGIH TLV	OSHA PEL	OTHER LIMITS	%
Alkyl Polymer	Mixture	NE	NE	NE	55-65
Ethylene glycol	107-21-1	50 ppm	NE	ceiling	< 10
Pigment	Mixture	NE	NE	NE	< 10
Water	7732-18-5	NE	NE	NE	38-48

## Section 3: Hazards Identification

### Emergency Overview

Appearance & Odor: Red paste, acrylic odor.

### Potential Health Effects:

Inhalation: NA  
Eyes: Irritation  
Skin: Irritation  
Ingestion: NA

Carcinogenicity: OSHA: No IARC: No NTP: No  
Chronic Overexposure: NA  
Medical Conditions Aggravated by Exposure: NA

## Section 4: First Aid Measures

**Inhalation:** Remove to fresh air. Give artificial respiration if necessary.  
**Eyes:** Flush with large amounts of water for 15 minutes.  
**Skin:** Remove contaminated clothing and wash area with soap and water.  
**Ingestion:** Call a physician. Induce vomiting.

**Section 5: Fire-Fighting Measures**

Flashpoint: None Method: TCC LEL: ND UEL: ND  
Extinguishing Media: None  
Hazardous Combustion Products: CO<sub>2</sub> and carbon monoxide (fire)  
Fire-fighting Instructions: Remove containers from fire area if possible. Use self-contained breathing apparatus for fire fighting.

NFPA: Health: 1 Flammability: 0 Reactivity: 0  
HMIS: Health: 1 Flammability: 0 Reactivity: 0 PPE: B

**Section 6: Accidental Release Measures**

Spill/Leak Procedures: Area should be ventilated. Absorbent should be used to pick up excess material. All used and unused product should be disposed of in accordance with federal, state and local regulations.

**Section 7: Handling and Storage**

Handling Procedures: Store in a cool, dry area.

**Section 8: Exposure Controls/Personal Protection**

Engineering Controls: Adequate to prevent accumulation of vapors. Use mechanical means if necessary to maintain levels below the exposure limits. If working in a confined space, follow applicable OSHA regulations.

Respiratory: Use NIOSH/MSHA compliant respirators or self-contained breathing apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.

Protective Clothing/Equipment: Wear chemically protective gloves and safety glasses. Use a splash apron and boots if splashing occurs.

**Section 9: Physical & Chemical Properties**

Physical State:	Liquid	Appearance & Odor:	Red paste, acrylic odor
Specific Gravity:	1.0487	Boiling Point:	c.a. 212°F
Freezing Point:	c.a. 32°F	Vapor Pressure:	ND
Evaporation Rate:	ND	Vapor Density (air = 1)	ND
pH:	NA	Solubility:	May be dispersed w/water.

Volatile Organic Compounds:%: 2.0 g/L: 21.221 lbs./gal: 0.177

**Section 10: Stability and Reactivity**

Stability: Stable Hazardous Polymerization: No  
Chemical Incompatibilities: Strong oxidizers.  
Materials to Avoid: NA  
Hazardous Decomposition Products: None

**Section 11: Toxicological Information**

Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

**Section 12: Ecological Information**

Ecotoxicity: No data available.  
Environmental Fate: No data available for biodegradation.

**Section 13: Disposal Considerations**

Disposal: This material if discarded may be hazardous waste under U.S. EPA RCRA regulations. All disposal activities must comply with federal, state and local regulations. Contact your local or state environmental agency for specific rules. Do not dump into sewers, on the ground or into any body of water.

**Section 14: Transportation Information**

Shipping Name: Consumer Commodity  
Hazard Class: ORM-D UN Number: NA Packing Group: NA  
Label: NA Placard: NA  
Special Provisions: NA

**Section 15: Regulatory Information**

TSCA: All components are either listed under TSCA or are exempt.  
SARA Title III: Section 311/312: NA Section 313\*: Ethylene glycol  
CERCLA/Superfund (RQ): NA  
Extremely Hazardous Substances: No  
California Prop 65: This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm.

\* See section 2 for percentage

**Section 16: Additional Information**

Prepared By: Adam M. Selisker Date: February 17, 1999  
Technical Information: (800) 521-3168 CRC #: 562A

This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS: Chemical Abstract Service NA: Not Applicable  
ppm: Parts per Million ND: Not Determined  
TCC: Tag Closed Cup NE: Not Established  
LEL: Lower Exposure Limit g/L: grams per Liter  
UEL: Upper Exposure Limit lbs./gal: pounds per gallon  
PPE: Personal Protection Equipment RQ: Reportable Quantity  
COC: Cleveland Closed Cup