

PRODUCT NAME: PORCH AND FLOOR BATTLESHIP GRET
PRODUCT CODE: 220145 (SEE ADDENDUM)

HHS CODES: H F R P
1 2 0

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: BENNETTE PAINT MANUFACTURING COMPANY INC.
ADDRESS: 401 Industry Drive, Hampton, Virginia 23661
EMERGENCY PHONE: 804-838-7777

DATE PREPARED: 12-13-88
INFORMATION PHONE: 804-838-7777
NAME OF PREPARER: Bennette Paint Mfg. Co., Inc.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS	CAS NUMBER	OSHA PEL	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE mm Hg @ 20°C	WEIGHT PERCENT
			ACGIH TLV	OTHER		
TITANIUM DIOXIDE	1328-20-7	100 ppm	100 ppm	150 ppm	25.0	77%
ETHYL BENZENE	100-41-4	100 ppm	100 ppm	NR	10.0	0%
METHYL ETHYL KETONE	8052-41-3	100 ppm	NR	NR	10.0	77%
PARAFFIN	1482-96-4	20 ppm	NR	NR	N/A	42.62%

This chemical is subject to the reporting requirement of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 316-380 deg F V.P.C.: 2.42 LB/EA (290 GR/L)
VAPOR DENSITY: HEAVIER THAN AIR SOLUBILITY IN WATER: Insoluble
APPEARANCE AND ODOR: Viscous liquid. Mild odor. WEIGHT PER GALLON: 8.32

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 105 deg F METHOD USED: TTC FLAMMABLE LIMITS IN AIR BY VOLUME: LOWER: 0.9% UPPER: 7.0%
SPECIAL FIREFIGHTING PROCEDURES: Use air-supplied rescue equipment for enclosed areas. Cool exposed containers with water spray. Avoid breathing vapor or fumes.

SECTION V - REACTIVITY DATA

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from heat, sparks, and open flames. Fight as volatile liquid fire. Use water to keep fire-exposed containers cool to reduce pressure.
STABILITY: Stable
CONDITIONS TO AVOID: Extreme heat or humidity. Any source of ignition.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Usual products of combustion-CO, CO2, and possible acrolein.

SECTION VI - HEALTH HAZARD DATA

IRITATION: HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Temporary dizziness, headache, possible nausea; symptoms disappear when exposure ceases.
SKIN AND EYE CONTACT: HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Eye or skin contact may cause discomfort by defatting action of solvent. Repeated contact to skin may cause dermatitis.
SKIN ABSORPTION: HEALTH RISKS AND SYMPTOMS OF EXPOSURE: See above
INGESTION: HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Do not ingest.
HEALTH HAZARDS (ACUTE AND CHRONIC): Inhalation: Temporary dizziness, headache, possible nausea; symptoms disappear when exposure ceases.

Eye or skin contact may cause discomfort by defatting action of solvent. Repeated contact to skin may cause dermatitis.
CARCINOGENICITY: N/A MUTY: No LACR MONITORING: No OSHA REGULATED: No

NEEDLE CONDITIONS GENERALLY ASSUMED BY EXPOSURE: Any existing respiratory or cardiovascular ailment.
EMERGENCY AND FIRST AID PROCEDURES: If overcome by vapor, remove from exposure immediately; call a physician. If breathing is irregular or stopped, start resuscitation, administer oxygen. If ingested, DO NOT induce vomiting; call a physician. In case of skin contact, remove contaminated clothing, and wash skin thoroughly. If splashed into eyes, flush eyes with clean water for 15 minutes or until irritation subsides. If irritation persists- seek medical attention.

STEPS TO BE TAKEN IF CASE MATERIAL IS RELEASED FOR SPILLED: Remove sources of ignition and provide ventilation. Large spills may be scooped up with non-sparking tools. Provide respiratory protection if required. Small quantities may be picked up with absorbent material.
WASTE DISPOSAL METHOD: In accordance with local, state, and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store away from heat, sparks, and open flame. Avoid prolonged skin contact. DO NOT breathe spray mist. Combustible liquid, class II.
OTHER PRECAUTIONS: Ground containers when pouring and lift free fall to a few inches to prevent static sparks. Avoid spontaneous combustion of contaminated rags and other easily ignitable organic accumulations by immediate immersion in water. Empty containers may retain hazardous properties. DO NOT cut, puncture, or weld on or near containers. Keep away from children.

RESPIRATORY PROTECTION: Approved mask or respirator for organic vapors.
VENTILATION: Ventilation should be designed and maintained to provide volume and pattern sufficient to prevent vapor concentration in excess of TLV or PEL.
PROTECTIVE GLOVES: Neoprene rubber gloves.

ETC PROTECTION: Goggles or side shield spectacles.
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye wash station and safety showers should be available.
WORK/HYGIENE PRACTICES: Wash hands after use and before eating or using washroom.

Bennette Paint Mfg. believes that the information contained in this MSDS is correct as of this date. However, because the material may be used under conditions over which Bennette Paint Mfg. has no control or in ways we can not anticipate, we give no warranty, expressed, or implied, as to the accuracy of the information and assume no responsibility for any damage.

APPROXIMATE DATE OF PREPARATION: 9-5-89
PRODUCT NUMBER: 220145, 220676
PRODUCT NAME: Porch and Floor Battleship Grey

Handwritten: 22-458
Bennette
update