

ITEM: 6A939 - Paint Striping White

PICK REQ: 1015522850

MATERIAL SAFETY DATA SHEET (MSDS)

MSDS: A7757

This MSDS should be attached or kept with the respective product with which it is associated.

MATERIAL SAFETY DATA SHEET - A7757

Related Grainger Item: 6A939 - Paint Striping White

MATERIAL SAFETY DATA SHEET

24 HOUR ASSISTANCE: 1-847-367-7700

RUST-OLEUM CORP.

WWW.RUSTOLEUM.COM

----- SECTION 1 - CHEMICAL PRODUCT/COMPANY INFORMATION -----

PRODUCT NAME:
RUST-OLEUM HIGH PERFORMANCE INDUSTRIAL ENAMEL AEROSOL - INVERTED STRIPING

REVISION DATE: 08/27/2004

IDENTIFICATION NUMBER: 2326838, 2348838, 2364838, 2378838, 2391838

PRODUCT USE/CLASS: INVERTED STRIPING PAINT/AEROSOL

SUPPLIER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USA

MANUFACTURER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USA

PREPARER: CZICZO, RAY

----- SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS -----

CHEMICAL NAME	CAS NUMBER	WEIGHT % LESS THAN	ACGIH TLV-TWA
LIQUIFIED PETROLEUM GAS	68476-86-8	25.0	1000 PPM
TITANIUM DIOXIDE	13463-67-7	15.0	10 MG/M3
ALIPHATIC HYDROCARBON	64742-89-8	10.0	300 PPM
TOLUENE	108-88-3	10.0	50 PPM
XYLENE	8032-32-4	10.0	300 PPM
ACETONE	67-64-1	5.0	500 PPM
STODDARD SOLVENTS	8052-41-3	5.0	100 PPM
PIGMENT BLACK 7	1333-86-4	5.0	3.5 MG/M3
AROMATIC HYDROCARBON	64742-95-6	5.0	N.E.
XYLENE	1330-20-7	5.0	100 PPM
1,2,4-TRIMETHYLBENZENE	95-63-6	5.0	25 PPM
ETHYLBENZENE	100-41-4	1.0	100 PPM

CHEMICAL NAME	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING
LIQUIFIED PETROLEUM GAS	N.E.	1000 PPM	N.E.
TITANIUM DIOXIDE	N.E.	10 MG/M3	N.E.
ALIPHATIC HYDROCARBON	N.E.	300 PPM	N.E.
TOLUENE	150 PPM	200 PPM	300 PPM
NAPHTHA	N.E.	N.E.	N.E.
ACETONE	750 PPM	750 PPM	N.E.
STODDARD SOLVENTS	N.E.	500 PPM	N.E.
PIGMENT BLACK 7	N.E.	3.5 MG/M3	N.E.
AROMATIC HYDROCARBON	N.E.	N.E.	N.E.
XYLENE	150 PPM	100 PPM	N.E.
1,2,4-TRIMETHYLBENZENE	N.E.	N.E.	N.E.
ETHYLBENZENE	125 PPM	100 PPM	N.E.

----- SECTION 3 - HAZARDS IDENTIFICATION -----

EMERGENCY OVERVIEW:
HARMFUL IF INHALED. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CONTENTS UNDER PRESSURE. VAPORS MAY CAUSE FLASH FIRE OR EXPLOSION. EXTREMELY FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAUSES EYE IRRITATION.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT:
PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION. SUBSTANCE MAY CAUSE SLIGHT SKIN IRRITATION.

EFFECTS OF OVEREXPOSURE - INHALATION:
HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES, NOSE, THROAT AND

LUNGS. AVOID BREATHING VAPORS OR MISTS. HIGH GAS, VAPOR, MIST OR DUST CONCENTRATIONS MAY BE HARMFUL IF INHALED. HARMFUL IF INHALED.

EFFECTS OF OVEREXPOSURE - INGESTION:
ASPIRATION HAZARD IF SWALLOWED; CAN ENTER LUNGS AND CAUSE DAMAGE. SUBSTANCE MAY BE HARMFUL IF SWALLOWED.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:
IARC LISTS ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B). MAY CAUSE CENTRAL NERVOUS SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO XYLENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY, LUNG, SPLEEN, EYE AND BLOOD DAMAGE AS WELL AS REPRODUCTIVE DISORDERS. EFFECTS IN HUMANS, DUE TO CHRONIC OVEREXPOSURE, HAVE INCLUDED LIVER, CARDIAC ABNORMALITIES AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO TOLUENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY, LUNG AND SPLEEN DAMAGE. EFFECTS IN HUMANS HAVE INCLUDED LIVER AND CARDIAC ABNORMALITIES. CONTAINS CARBON BLACK. CHRONIC INFLAMMATION, LUNG FIBROSIS, AND LUNG TUMORS HAVE BEEN OBSERVED IN SOME RATS EXPERIMENTALLY EXPOSED FOR LONG PERIODS OF TIME TO EXCESSIVE CONCENTRATIONS OF CARBON BLACK AND SEVERAL INSOLUBLE FINE DUST PARTICLES. TUMORS HAVE NOT BEEN OBSERVED IN OTHER ANIMAL SPECIES (I.E., MOUSE AND HAMSTER) UNDER SIMILAR CIRCUMSTANCES AND STUDY CONDITIONS. EPIDEMIOLOGICAL STUDIES OF NORTH AMERICAN WORKERS SHOW NO EVIDENCE OF CLINICALLY SIGNIFICANT ADVERSE HEALTH EFFECTS DUE TO OCCUPATIONAL EXPOSURE TO CARBON BLACK. CARBON BLACK IS LISTED AS A GROUP 2B - "POSSIBLY CARCINOGENIC TO HUMANS" BY IARC AND IS PROPOSED TO BE LISTED AS A4 - "NOT CLASSIFIED AS A HUMAN CARCINOGEN" BY THE AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS. SIGNIFICANT EXPOSURE IS NOT ANTICIPATED DURING BRUSH APPLICATION OR DRYING. RISK OF OVEREXPOSURE DEPENDS ON DURATION AND LEVEL OF EXPOSURE TO DUST FROM REPEATED SANDING OF SURFACES OR SPRAY MIST AND THE ACTUAL CONCENTRATION OF CARBON BLACK IN THE FORMULA.

PRIMARY ROUTE(S) OF ENTRY:
SKIN CONTACT, SKIN ABSORPTION, INHALATION, EYE CONTACT

----- SECTION 4 - FIRST AID MEASURES -----

FIRST AID - EYE CONTACT:
HOLD EYELIDS APART AND FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT:
WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

FIRST AID - INHALATION:
IF YOU EXPERIENCE DIFFICULTY IN BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY.

FIRST AID - INGESTION:
ASPIRATION HAZARD:
DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION.

----- SECTION 5 - FIRE FIGHTING MEASURES -----

FLASH POINT: -156 F (SETAFLASH)

LOWER EXPLOSIVE LIMIT: 1.0%
UPPER EXPLOSIVE LIMIT: 12.8%

EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM, WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:
VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. WATER SPRAY MAY BE INEFFECTIVE.
FLASH POINT IS LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR!
PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. KEEP CONTAINERS TIGHTLY CLOSED.

SPECIAL FIREFIGHTING PROCEDURES:
EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE.

----- SECTION 6 - ACCIDENTAL RELEASE MEASURES -----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:
CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL, STATE (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

----- SECTION 7 - HANDLING AND STORAGE -----

HANDLING:
WASH THOROUGHLY AFTER HANDLING. WASH HANDS BEFORE EATING. USE ONLY IN A WELL-VENTILATED AREA. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. AVOID BREATHING VAPOR OR MIST.

STORAGE:
KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120 DEG. F.

----- SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION -----

ENGINEERING CONTROLS:

USE EXPLOSION-PROOF VENTILATION EQUIPMENT. PREVENT BUILD-UP OF VAPORS BY OPENING ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION. USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS.

RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH AN AIR PURIFYING VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS.

PROTECTION PROVIDED BY AIR PURIFYING RESPIRATORS IS LIMITED. USE A POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR IF THERE IS ANY POTENTIAL FOR AN UNCONTROLLED RELEASE, EXPOSURE LEVELS ARE NOT KNOWN, OR ANY OTHER CIRCUMSTANCES WHERE AIR PURIFYING RESPIRATORS MAY NOT PROVIDE ADEQUATE PROTECTION.

SKIN PROTECTION:

USE IMPERVIOUS GLOVES TO PREVENT SKIN CONTACT AND ABSORPTION OF THIS MATERIAL THROUGH THE SKIN. NITRILE OR NEOPRENE GLOVES MAY AFFORD ADEQUATE SKIN PROTECTION.

EYE PROTECTION:

USE SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

OTHER PROTECTIVE EQUIPMENT:

REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER INFORMATION REGARDING PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION.

HYGIENIC PRACTICES:

WASH THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING OR SMOKING.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE: 130 - 410 F

VAPOR DENSITY: HEAVIER THAN AIR

ODOR: SOLVENT LIKE

ODOR THRESHOLD: ND

APPEARANCE: LIQUID

EVAPORATION RATE: FASTER THAN ETHER

SOLUBILITY IN H₂O: SLIGHT

FREEZE POINT: ND

SPECIFIC GRAVITY: 0.9700

VAPOR PRESSURE: ND

PH: NE

PHYSICAL STATE: LIQUID

REFER TO SECTION 16 FOR ABBREVIATION LEGEND

SECTION 10 - STABILITY AND REACTIVITY**CONDITIONS TO AVOID:**

AVOID ALL POSSIBLE SOURCES OF IGNITION. AVOID TEMPERATURES ABOVE 120 DEG. F.

INCOMPATIBILITY:

INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS AND STRONG ALKALIES.

HAZARDOUS DECOMPOSITION:

WHEN HEATED TO DECOMPOSITION IT EMITS ACRID SMOKE AND IRRITATING FUMES. BY OPEN FLAME, CARBON MONOXIDE AND CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

SECTION 11 - TOXICOLOGICAL INFORMATION

PRODUCT LD₅₀: ND

PRODUCT LC₅₀: ND

CHEMICAL NAME	LD50	LC50
LIQUIFIED PETROLEUM GAS	N.D.	N.D.
TITANIUM DIOXIDE	>7500 MG/KG (ORAL, RAT)	N.D.
ALIPHATIC HYDROCARBON	N.D.	N.D.
TOLUENE	N.D.	N.D.
NAPHTHA	>5000 MG/KG (ORAL, RAT)	N.D.
ACETONE	N.D.	N.D.
STODDARD SOLVENTS	N.D.	N.D.
PIGMENT BLACK 7	>8000 MG/KG (ORAL, RAT)	N.D.
AROMATIC HYDROCARBON	N.D.	N.D.
KYLENE	N.D.	N.D.
TRIMETHYLBENZENE	N.D.	18000 MG/M3 (RAT, 4 HR)
ETHYLBENZENE	3500 MG/KG (ORAL, RAT)	N.D.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

SECTION 13 - DISPOSAL INFORMATION**DISPOSAL INFORMATION:**

DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER STORM DRAINS OR SEWER SYSTEMS.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: AEROSOL

DOT TECHNICAL NAME:

DOT HAZARD CLASS: 2

DOT UN/NA NUMBER: UN 1950

PACKING GROUP:

HAZARD SUBCLASS: 1

RESP. GUIDE PAGE: 126

SECTION 15 - REGULATORY INFORMATION**CERCLA - SARA HAZARD CATEGORY:**

THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA "HAZARD CATEGORIES" PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES: IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD

SARA SECTION 313:

LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CHEMICAL NAME	CAS NUMBER
TOLUENE	108-88-3
XYLENE	1330-20-7
1,2,4-TRIMETHYLBENZENE	95-63-6
ETHYLBENZENE	100-41-4

TOXIC SUBSTANCES CONTROL ACT:

LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES: NONE KNOWN

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE COMPONENTS IN THIS PRODUCT.

CHEMICAL NAME	CAS NUMBER
CALCIUM CARBONATE	1317-65-3
MODIFIED ALKYD	PROPRIETARY

PENNSYLVANIA RIGHT-TO-KNOW:

THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%.

CHEMICAL NAME	CAS NUMBER
CALCIUM CARBONATE	1317-65-3
MODIFIED ALKYD	PROPRIETARY

CALIFORNIA PROPOSITION 65:**WARNING:**

THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

CHEMICAL NAME	CAS NUMBER
ETHYLBENZENE	100-41-4
MICROCRYSTALLINE SILICA	14808-60-7
FORMALDEHYDE	50-00-0
BENZENE	71-43-2
ARSENIC COMPOUNDS	NOT SPECIFIED
CADMIUM COMPOUNDS	NOT SPECIFIED
ACETALDEHYDE	75-07-0
NICKEL COMPOUNDS	NOT SPECIFIED
LEAD COMPOUNDS	NOT SPECIFIED

WARNING:

THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS, OR OTHER REPRODUCTIVE HAZARDS.

CHEMICAL NAME	CAS NUMBER
TOLUENE	108-88-3
BENZENE	71-43-2
ARSENIC COMPOUNDS	NOT SPECIFIED
CADMIUM COMPOUNDS	NOT SPECIFIED
MERCURY COMPOUNDS	NOT SPECIFIED

LEAD COMPOUNDS NOT SPECIFIED

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS:
THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT
REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS:

SECTION 16 - OTHER INFORMATION

HMS RATINGS:
HEALTH: 2*
FLAMMABILITY: 4
REACTIVITY: 0
PERSONAL PROTECTION: X

VOLATILE ORGANIC COMPOUNDS, G/L: 523 MAX

REASON FOR REVISION:

LEGEND:
N.A. - NOT APPLICABLE
N.E. - NOT ESTABLISHED
N.D. - NOT DETERMINED

THE INFORMATION CONTAINED ON THIS MSDS HAS BEEN CHECKED AND SHOULD BE
ACCURATE. HOWEVER, IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL
FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.