

I Chemical Product and Company Identification	Product Name CLAIRE DISINFECTANT SPRAY		Emergency (800)831-9889	
	Product Code 32512279	UPC-A SCC	Medical(Collect) (303)592-1024	
II Composition/ Information on Ingredients	Manufacturer AMERICLEAN SYSTEMS, INC. 26935 NORTHWESTERN HWY, SUITE 400 SOUTHFIELD, MI 48034		Chemtree (800)424-9300	
	Date 09/17/1998			
Chemical Family PRESSURIZED CLEANER				
III Hazards Identification	Chemical Name of Hazardous Ingredient	%	Exposure Limits	Units
	ORTHOPHENYLPHENOL-CAS#90-43-7 PARA-TERTIARY AMYLPHENOL-CAS#80-46-6 METHYL ALCOHOL-CAS#67-56-1 ETHYL ALCOHOL-CAS#64-17-5 SODIUM NITRITE-CAS#7632-00-0 AMMONIUM HYDROXIDE-CAS#1336-21-6 EPA REGISTRATION#706-69	<1 <1 <1 <1	NONE ESTABLISHED NONE ESTABLISHED TLV 200; PEL 200 TLV 1000; PEL 1000 NONE ESTABLISHED TLV 25; PEL 50	PPM
III Hazards Identification	Signs and Symptoms of Exposure RESPIRATORY IRRITATION. HIGH CONCENTRATIONS MAY CAUSE DRYING OR IRRITATION OF SKIN. MAY BURN OR IRRITATE EYES.			
	SAME AS ACUTE			
	HMIS: Health 1 Flammability 4 Reactivity 0 Personal Protection A			
	Conditions Aggravated SENSITIVE SKIN AND EYES			
	Carcinogen Info NONE NTP IARC OSHA			
	Target Organs or System			
IV First Aid Measures	Routes of Exposure: Inhalation <input checked="" type="checkbox"/> Skin <input checked="" type="checkbox"/> Ingestion <input checked="" type="checkbox"/>			
	Inhalation N/A IN NORMAL OPERATIONS			
	Eyes	QUICKLY FLUSH EYES WITH WATER, REMOVE ANY CONTACT LENSES, THEN HOLD EYE LIDS OPEN AND FLUSH EYES THOROUGHLY WITH FRESH WATER, CONTINUING FOR AT LEAST 15 MINUTES.		
	Skin	FLUSH WITH FRESH WATER FOR AT LEAST 15 MINUTES, WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHES AND SHOES.		
Ingestion GIVE WATER, INDUCE VOMITING. GET MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.				
V Fire Fighting Measures	Fire Control Measures/ Equipment	HEAT COULD BURST PRESSURIZED CANS. KEEP AWAY FROM HEAT, DIRECT SUNLIGHT, OPEN FLAMES OR SPARKS.		
	Flammable Property Info	FLAMMABLE 16 CFR 1500.45		
	Explosion Info	IN A FIRE SITUATION, CONTAINERS SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESSURE BUILD UP.		
	Extinguishing Media	CO2, FOAM, DRY CHEMICALS		
	Gases	CARBON MONOXIDE, CARBON DIOXIDE		

