

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	Heat and ignition sources; storage under inert atmosphere; contamination.

Incompatibility (Materials to Avoid)

Reducing and oxidizing agents. Material has strong properties and can soften paint or rubber

Hazardous Decomposition or Byproducts

Hazardous decomposition products: CO, CO₂, smoke

Hazardous Polymerization	May Occur	X	Conditions to Avoid
	Will Not Occur		Excessive heat, storage in absence of inhibitor; inadvertent addition of catalyst. See E-53033 for details on inhibitors and storage stability.

Section VI — Health Hazard Data

Route(s) of Entry: _____ Ingestion? _____
Symptoms/effects of overexposure and first aid _____ Skin? _____ Ingestion? _____

Health Hazards (Acute and Chronic)

Carcinogenicity: _____ NTP? _____ IARC Monographs? _____ OSHA Regulated? _____
None known at this time.

Signs and Symptoms of Exposure

INGESTION: Induce vomiting and get prompt medical attention. Low oral toxicity. INHALATION: Overexposure may cause eye, nose and respiratory tract. May cause central nervous system effects such as dizziness, headache, nausea and loss of consciousness. Remove to fresh air. SKIN OR EYE CONTACT: Vapor may cause irritation of the eyes, liquid may cause moderate irritation. Repeated or prolonged contact may cause allergic skin rash, itching, swelling. In case of eye contact, immediately flush with plenty of water for at least 15 minutes; call a physician.

Emergency and First Aid Procedures

— If having breathing difficulty, administer oxygen. If not breathing, administer artificial respiration. Call a physician. In case of skin contact, wash with soap and water. If irritation occurs, contact a physician.

Section VII — Precautions for Safe Handling and Use**Steps to Be Taken in Case Material is Released or Spilled**

Evacuate area. Remove sources of ignition. Prevent skin contact and breathing of vapor.

Confine and remove with inert absorbant. Ventilate area.

Waste Disposal Method

— EPA listed hazardous waste under RCRA (U-118). Do not allow material to contaminate ground water systems. Incinerate in a facility which complies with federal, state and local requirements. Do not incinerate in closed containers.

Precautions to Be Taken in Handling and Storing

— Observe label precautions. Keep away from heat, direct sunlight, sparks and flame. Close container after each use. Ground containers when pouring. See E-53033. Regulations related to storage of flammable liquids should be followed.

Other Precautions

Permit air space to exist inside storage containers. Materials stored more than 3 months should have inhibitor level checked and maintained at the original level.

Section VIII — Control Measures**Respiratory Protection (Specify Type)**

When levels exceed 100PPM, wear self-contained breathing apparatus.

Ventilation	Local Exhaust	Special
	Mechanical (General)	Other

Protective Gloves: Neoprene gloves are recommended. Eye Protection: Splashproof goggles.

Other Protective Clothing or Equipment: Neoprene boots and coveralls.

Work/Hygiene Practices